Harlequin

Standfast

Harlequin Standfast is a durable multi-purpose homogeneous vinyl performance floor with a slip-resistant surface. It is is an ideal heavy-duty floor for studios as well as stage flooring for dance studios and theatres.

Installation: Harlequin Standfast is specified for permanent installation, the joins are heat welded to form a continuous performance surface. It can be laid on any hard, smooth subfloor and is an excellent choice as a vinyl performance surface in conjunction with a Harlequin sprung floor.

Usage: Harlequin Standfast is suitable for theatre, drama and many genres of dance including percussive dance (flamenco, Irish and tap), hip-hop, jazz, street and Zumba. It is also ideal as a multi-use stage floor.

Specification Guide

Material	Homogeneous vinyl
Permanent or Portable	Permanent
Roll Lengths	10m, 15m, 20m
Roll Width	1.5m
Thickness	2.6mm
Weight	3.4kg/m ²
Finish	Smooth
Fire Rating	Cfl-s1 (EN 13501-1)
Warranty	10 years if installed by Harlequin 5 years if installed by the customer
Impact Sound Reduction	3dB, with Activity sprung floor 22dB
Fixing Type	Adhesive
Seams	Welded
Light Reflectance	406-8, 501-2, 004-28
Gloss Level	Nominal 6
Lightfastness	>6
Recycled Content	23-30%
VOC Emissions	≤0.5mg/m³
Recyclability	100%
Underfloor Heating	Suitable for use with underfloor heating
Third Party Certification	Environmental Product Declaration A+ LEED, BREEAM, REACH Compliant





Homogeneous vinyl with a slip-resistant performance surface

Grey - 004



Black - 501









