Harlequin Studio M

Harlequin Studio is a hardwearing, slip-resistant, vinyl performance floor that features a lightweight closed-cell foam backing to provide protection against hard sub-floors, it is ideal as a multi-purpose dance or stage floor.

Installation: Harlequin Studio is specified for permanent or temporary installation, the joins are welded to form a continuous performance surface and is recommended for use in conjunction with a suitable Harlequin sprung floor.

Usage: Harlequin Studio is suitable for ballet, contemporary and modern dance. It is also used for aerobics, hip-hop, jazz and street dance.




All Harlequin vinyl floors are 100% recyclable.

Specification Guide

| Material | Heterogeneous vinyl |
|---------------------------|---|
| Permanent or Portable | Both |
| Roll Lengths | 10m, 15m, 18m, 20m, 25m, 30m |
| Roll Width | 1.5m |
| Thickness | 3mm |
| Weight | 2.3kg/m² |
| Finish | Smooth |
| Fire Rating | Bfl-s1 (EN 13501-1) |
| Warranty | 10 years if installed by Harlequin |
| | 5 years if installed by the customer |
| Impact Sound Reduction | 6dB, with Harlequin Activity sprung floor 22dB |
| Fixing Type | Adhesive or Tape |
| Seams | Welded or Taped |
| Light Reflectance | 180-2, 880-41, 890-20, 100-87 |
| Gloss Level | Nominal 6 |
| Lightfastness | >6 |
| Recycled Content | 23-30% |
| VOC Emissions | ≤0.5mg/m³ |
| Recyclability | 100% |
| Underfloor Heating | Suitable for use with underfloor heating |
| Third Party Certification | Environmental Product Declaration A ⁺ LEED, BREEAM, REACH Compliant |

Available Colours:

Black - 180













IB ANDERSEN ARTISTIC DIRECTOR



If you would like further information or advice please contact us on +61 (2) 9620 7770 or auscontact@harlequinfloors.com

The Company reserves the right to make any variation in design or construction of the material described. Harlequin ® is a registered trademark of British Harlequin plc. ® Harlequin Floors 09/2024



northern ballet

